

Wood Oil Precious Wood Oil

Product properties

Oil-based water-repellent wood oil, which is particularly suitable for the care of various types of exotic wood. Penetrates into the wood and protects the wood from drying out and cracking, so it lasts longer. Prevents the formation of mould and mould growth on the surface.

Product use

Used for outdoor wood, e.g. teak, mahogany or nyatoh, where you want to preserve the wood's natural glow. For example, garden furniture, wooden terraces, windows, etc.



Substrate

The substrate must be clean, dry, firm, and not previously treated with varnish or paint.

Application

Algae, mould and mildew must be removed by cleaning with Facade Cleaner.

Clean with basic cleaner.

Sand glossy surfaces matt.

Stir before and during use.

Apply 1-2 times with a brush, wet on wet until the wood is saturated, especially on joints and end wood.

Wipe off excess wood oil in order to avoid varnish layers which may peel off later.

Good practise

Avoid working in direct sunlight.

The surface should be inspected once a year and maintained if necessary.

Environmental information

Remove as much paint as possible from tools before cleaning. Do not pour leftover liquid paint down the drain, hand it in at the local recycling station. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost free and tightly closed

Technical Data

| | |
|---|------------------------|
| Product Type | Wood Oil |
| Density (kgs/l) | 0.92 |
| Solids Weight % | 57 |
| Solids Vol. % | 50 |
| Nominal spreading rate (m ² /ltr.) | 8 |
| Long spreading rate (m ² /l) | 10 |
| Short Spreading rate (m ² /l) | 4 |
| Min. working temp. during application and drying/curing | Min. +5°C |
| Humidity | Max. humidity 80 % RH. |
| Drying time at 20° C, 60 % RH (Hours) | 4 |
| Recoatable at 20° C, 60 % RH (Hours) | 12 |
| Fully cured at 20° C, 60 % RH (Days) | 28 |
| Dilution | Do not dilute |
| Cleaning of Tools etc. | White spirit |

Current TDS Version

December 2021

Replaces TDS Version

May 2021