

# Wall Paint Acrylplast 5

## Product properties

Matt acrylic paint for walls and ceilings. Gives a matt surface with good adhesion. Extra good hiding power and quick to work with. Not suitable for surfaces with high demands on robustness.

## Product use

For new and previously painted ceilings and walls indoors.  
On concrete, plaster, wallpaper, glass tissue and felt in living rooms and other living spaces.



## Substrate

The substrate must be clean, dry, firm and sustainable.

## Application

Clean previously painted surfaces with Basic Cleaner.  
Fill any cracks and holes with filler.  
Prime with sealer if the surface is chalking or is very absorbent.  
Prime any stains from water damage or tobacco with blocking primer.  
Prime chalking and porous surfaces with Yunix Pro Priming Paint.  
Apply 1-2 coats of paint with a brush, roller or sprayer.  
Remember to ventilate after painting.

## Environmental information

Minimize your paint waste by pre-estimating how much paint you need.  
Remove as much paint as possible from tools before cleaning.  
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.  
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.  
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

**Storage:** Cool, frost free and tightly closed

**Protection equipment:** Protect skin and eyes from splashes with suitable clothing, gloves and glasses. Avoid inhalation of spray mist and grinding dust. Wear suitable protective equipment, see safety data sheet for further information.

# Technical Data

---

Gloss	Matte;5
Density (kgs/l)	1.42
Solids Weight %	53
Solids Vol. %	34
Nominal spreading rate (m <sup>2</sup> /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	2
Fully cured at 20° C, 60 % RH (Days)	28
Washability acc. to EN-13300/ISO-11998	Class 2
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water

---

## Current TDS Version

May 2024

## Replaces TDS Version

December 2021