

Pro Iso Paint 5

Product properties

Matt wall and ceiling paint with blocking properties against the penetration of water-soluble colourants.

Labelling



Product use

For new and previously painted surfaces indoors where there is a risk of strike-through, e.g. from soot, nicotine and dry water stains.

On concrete, lightweight concrete, plaster, gypsumboards, fibre plaster, cement fibre boards, cement chipboard.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Dirt, grime, grease and chalking material are removed with basic cleaner.

Water-soluble discolouration, nicotine and soot must be cleaned.

Hard, smooth surfaces should be sanded matt.

Cracks, unevenness and holes must be spackled.

Absorbent and porous substrates must be primed with sealer.

Apply 1-2 times depending on strike-through.

Remember to ventilate after painting.

Application

Brush or roller.

Decide your choice of tool/utensil depending on the finish.

Apply wet on wet and finish by brushing/rolling in the same direction.

Always use the same batch number on contiguous/unbroken surfaces.

Differences in surface structure can result in colour deviation.

Cold/heat can affect the viscosity of the material.

Condensation during drying/curing must not occur.

Cold and increased humidity extends drying time, full curing and recoat interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of Function and finish.

Good practice

If repairs are needed, remove minor marks and dirt by cleaning.

Spot repairs are carried out with the same material/batch number as originally used.

Spot repairs are expected to be visible to a greater or lesser extent depending on colour, gloss, application method, surface, light and viewing angle.

Larger damages are repaired with edging around corners, joints and the like.

Expected result

Matt surface with a low gloss.

Exercise care in loading the surface until the paint is fully cured.

The blocking effect is reduced if the product is tinted.

Cleaning and maintenance

Withstands cleaning with mild detergents without abrasives, water and wiping with a damp cloth.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Gloss	Matte;5
Density (kgs/l)	1.47
Solids Weight %	62
Solids Vol. %	45
Nominal spreading rate (m²/ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Recoatable at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Washability acc. to EN-13300/ISO-11998	Class 1
Dilution	Do not dilute
Cleaning of Tools etc.	Water
Country of Origin	Denmark

Current TDS Version

October 2025