

Product properties

Transparent blue-toned primer with good penetration. Provides effective base and adhesive surface on mildly chalking and absorbent substrates. Use before painting indoors and outdoors or before installing wall coverings.

Product use

Priming of plaster, concrete, cardboard-coated gypsum board and plastered surfaces before installing wall coverings or painting with ceiling and wall paint.

Priming of slightly chalky and absorbent mineral facades, e.g. plaster, concrete and lightweight concrete before treatment with facade paint.



Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Precipitations, loose material and paint are removed by washing, cleaning and sanding.

Dirt, grime, grease and smudges indoors are cleaned with Basic Cleaner and outdoors with Facade Clean.

Water-soluble discolouration, nicotine and soot are cleaned with Soot and Nicotine Cleaner.

Algae, mould and mildew growth are removed by cleaning with Facade Algae Remover.

Sand the substrate as required.

Cracks, unevenness and holes are filled.

Larger cracks must be filled with suitable material.

Application

Apply with brush, roller or spray.

Decide your choice of tool/utensil depending on the finish.

Material temperature for spray painting, min. 12°C.

Condensation during drying/curing must not occur.

Avoid working in direct sunlight and on hot surfaces.

Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Uniform, saturated and transparent surface.

The surface must not appear glossy after application.

Finish treatment immediately after drying.

Please note!

Protect freshly painted surface from adverse weather conditions.

Take appropriate measures against the effects of moisture and rainfall on freshly painted surfaces.

It is important to apply a suitable layer thickness so that the substrate is saturated but does not appear glossy after drying.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.
Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.
Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost-free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Density (kgs/l)	1.03
Solids Weight %	13
Solids Vol. %	11
Nominal spreading rate (m²/ltr.)	5
Long spreading rate (m²/l.)	7
Short Spreading rate (m²/ltr.)	3
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	3
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Water
Country of Origin	Denmark

Current TDS Version

September 2025