

Pro Wall Paint 5

Product properties

Matt wall and ceiling paint with good hiding power. Recommended for premises with normal functional requirements that are exposed to moderate dirt and use-related wear.

Labelling



Product use

For new and previously painted surfaces indoors.

On concrete, lightweight concrete, plaster, gypsumboards, fibre plaster, cement fibre boards, cement chipboard.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Previously painted surfaces are cleaned with basic cleaner.

Prime stains from water damage or tobacco with a blocking primer.

Hard, smooth surfaces should be sanded matt and primed when needed.

Cracks, unevenness and holes must be spackled.

Absorbent and porous substrates must be primed with sealer.

Priming is performed with Wall Primer or Yunik Pro Wall Paint 5.

Apply 1-2 coats. Some colours and surfaces require an extra treatment.

Remember to ventilate after painting.

Application

Brush, roller or spray.

Decide your choice of tool/utensil depending on the finish.

Apply wet on wet and finish by brushing/rolling in the same direction.

Always use the same batch number on contiguous/unbroken surfaces.

Differences in surface structure can result in colour deviation.

Cold/heat can affect the viscosity of the material.

Material temperature for spray painting, min. 12°C.

Condensation during drying/curing must not occur.

Cold and increased humidity extends drying time, full curing and recoat interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of adhesion and result.

Good practice

If repairs are needed, remove minor marks and dirt by cleaning.

Spot repairs are carried out with the same material/batch number as originally used.

Spot repairs are expected to be visible to a greater or lesser extent depending on colour, gloss, application method, surface, light and viewing angle.

Larger damages are repaired with edging around corners, joints and the like.

Expected result

Matt surface with subdued gloss.

Strong especially dark shades are more delicate than light by wear and touch.

Chalking from strong shades due to excess pigment may occur.

Does not block strike-through from knots or water-soluble colourants, water stains and nicotine.

Exercise care in loading the surface until the paint is fully cured.

Cleaning and maintenance

Withstands cleaning with mild detergents without abrasives, water and wiping with a damp cloth.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Gloss	Matte;5
Density (kgs/l)	1.49
Solids Weight %	61
Solids Vol. %	42
Nominal spreading rate (m²/ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Washability acc. to EN-13300/ISO-11998	Class 2
Dilution	Water, is usually not diluted
Cleaning of Tools etc.	Water
Country of Origin	Denmark

Current TDS Version

October 2025

Replaces TDS Version

September 2025